

DECLARATION OF PERFORMANCE



DoP RTA8EN16-1 | 300WB-140

1. Unique identification code of the product-type: RAVATHERM XPS 300 WB
2. Type, id. number: RAVATHERM XPS 300 WB, 3002214020
Thickness: 140 mm
3. Intended use of the construction product as foreseen by the manufacturer: Thermal Insulation for Buildings (ThIB)
XPS/EN13164 - 2012
4. Name and contact address of the manufacturer: RAVATHERM Hungary Kft.
8184 Balatonfűzfő, Almádi út 4.
5. System or systems of assessment and verification of constancy of: AVCP - System 3
6. Name and identification number of notified body: FIW (0751)/L1-14-017D
ÉMI (1415)/M1-7188N-02653/M1-7188N-02608
7. Declared Performance: Essential characteristic (EN 13164 - ZA1)

Essential characteristic	Performance
Thermal conductivity	$\lambda_d = 0,035 \text{ W/mK}$
Thermal resistance	$R_d = 4,00 \text{ m}^2\text{K/W}$
Dimensional tolerances	T1
Compressive strength	CS(10\Y) 300
Tensile strength perpendicular to faces	TR400
Shear strength	SS NPD
Reaction to fire	E
Continuous glowing combustion	- -
Long term water absorption by total immersion	WL(T) 0,7
Long term water absorption by diffusion	WD(V) NPD
Water vapor diffusion resistance factor	MU 50
Durability of compressive strength against (compressive creep)	CC (2/1,5/50) NPD
Durability of reaction to fire against heat, weathering, ageing/degradation	No change in Reaction to fire properties for extruded polystyrene foam
Durability of thermal resistance against heat, weathering, ageing/degradation	
Thermal resistance and thermal conductivity	see above R_d and λ_d
Freeze/thaw resistance after long term water absorption by diffusion	FTCD NPD
Freeze/thaw resistance after long term water absorption by total immersion	FTCI NPD
Dimensional stability under specified temperature and humidity conditions	DS (70,90)
Deformation under specified compressive load and temperature conditions	DLT (2)5
Release of dangerous substances to the indoor environment	- -

8. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 7. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by

Gerendi Gábor
TS&D Manager

Balatonfűzfő, 28. January 2016.

NPD - No Performance Determined