## RAVATHERM™ XPS X 300 SL



## Technical data sheet

| Properties   |      |     |     |     |          | Value  |        |      |            | Unit      |          | Standard   |       | EN13164<br>Designation<br>Code |      |
|--|------|-----|-----|-----|----------|--------|--------|------|------------|-----------|----------|------------|-------|--------------------------------|------|
| Thermal Conductivity Declared  |      |     |     | 0.  | 030      | < 60mm |        |      | W/m.K      |           | EN 13164 |            | λ     | )                              |      |
|  |      |     |     |     | 0.       | 031    | ≥      | 60mm |            | W/m.K     |          |            |       |                                |      |
| Compressive stress or compressive strength@ 10% deformation                              |      |     |     |     | 3        | 800    |        |      |            | kPa       |          | EN 826     |       | CS(10\Y)                       |      |
| Compressive Creep max after 50 years < 2% deformation under stress $\sigma\text{C}$      |      |     |     |     | 1        | 30     |        |      |            | kPa       |          | EN 1606    |       | CC(2/1.5/50)σ                  |      |
| Water vapour diffusion resistance factor $\boldsymbol{\mu}$ (tabulated value)            |      |     |     |     | 1        | 50     |        |      |            | -         |          | EN 12086   |       | MU                             |      |
| Long term water absorption by total immersion  |      |     |     |     | <        | 0.7    |        |      |            | %         |          | EN 12087   |       | WL(T)                          |      |
| Water pick-up by diffusion   |      |     |     |     | < 2      | 50     | < 80mm |      | %          |           | EN 12088 |            | WD(V) |                                |      |
|  |      |     |     |     |          | < 1    | ≥      | 80mm |            |           |          |            |       |                                |      |
| Water pick up after Freeze Thaw  |      |     |     |     |          | < 1    |        |      | % EN 12091 |           | 091      | FTCD       |       |                                |      |
| Dimensional stability under specified temperature (70°C) and humidity conditions (90%rh) |      |     |     |     |          | < 5    |        |      | % EN 1604  |           | 04       | DS(70,90)  |       |                                |      |
| Coefficient of linear thermal expansion (typical value)                                  |      |     |     |     | 0.07     |        |        |      | mm/(m.K)   |           | )        | -          |       | -                              |      |
| Fire Performance   |      |     |     |     | E        |        |        | Er   |            | Euroclass |          | EN 13501-1 |       |                                |      |
| Temperature limits   |      |     |     |     | -50/+75  |        |        |      |            | °C        |          | -          |       |                                |      |
| Thickness tolerances   |      |     |     |     | 1        |        |        |      |            | Class     |          | EN 823     |       | Т                              |      |
| Dimensions Width   |      |     |     | 6   | 000      |        |        |      | mm         |           | EN 822   |            |       |                                |      |
| Length   |      |     |     |     | 1250     |        |        |      |            | mm        |          | EN 822     |       |                                |      |
| Edge Profile   |      |     |     |     | Ship lap |        |        |      |            |           |          |            |       |                                |      |
| Surface finish   |      |     |     |     | Skin     |        |        |      |            |           |          |            |       |                                |      |
| Thermal resistance <sup>1</sup>  |      |     |     |     |          |        |        |      |            |           |          |            |       |                                |      |
| Thickness(mm)  | 50   | 80  | 100 | 115 | 120      | 130    | 140    | 145  | 160        | 165       | 175      | 180        | 190   | 195                            | 200  |
| R <sub>d</sub> m².K/W  | 1.65 | 2.6 | 3.2 | 3.7 | 3.85     | 4.2    | 4.5    | 4.65 | 5.15       | 5.3       | 5.6      | 5.8        | 6.15  | 6.25                           | 6.45 |

Material shall be stored inside in original packaging, away from direct sun light or heat sources

Note: The information and data contained in this technical data sheet do not represent exact sales specifications. The features of the products mentioned may vary. The information contained in this document has been provided in good faith, however it does not imply any liability, guarantee or assurance of product performance. It is the purchaser's responsibility to determine whether these products are suitable for the application desired and to ensure that the site of work and method of application conform with current legislation. No license is hereby granted for the use of patents or other industrial or intellectual property rights. If products are purchased, we advise following the most up-to-date suggestions and recommendations.





<sup>1)</sup> Thickness dependant

<sup>1</sup> N/mm<sup>2</sup> = 10<sup>3</sup> kPa = 1MPa